

WPC750 is an easy to use, fast acting, concentrated synthetic acid descaler/cleaner. It is designed for cleaning pre-cast concrete, concrete, masonry, grout, limestone, marble, travertine and other stone. On these surfaces it will remove rust and lime deposits, hard water deposits, efflorescence, oil stains, common black and green algae, red clay stains, common dirt and grime stains and household food and liquid stains. WPC750 will penetrate below surface and lift dirt and soil from cementous and limestone substrates and certain stone. It will clean and slightly etch concrete and limestone opening the pores in preparation for sealing. It will also remove cement, grout haze, mortar residue and joint cement, and other mineral based deposits from most surfaces including natural stone. It is a conservative, less volatile alternative to acid-base cleaners for concrete, tile, grout and natural stone surfaces. It is suitable for interior and exterior use.

Use On

Concrete	Limestone
Pre-Cast Concrete Paver	Marble Tumbled & Honed
Masonry	Travertine
Cast Stone	Cleft & Honed Slate
Grout	Porcelain Tile
	Unglazed Ceramic Tile

APPLICATION

1. Read entire instructions before using. **Do not use on polished surfaces.** Keep out of reach of children.
2. Rubber gloves and eyes protection should be worn. If cleaner comes in contact with skin, wash immediately with soap and water.
3. **ALWAYS TEST A SMALL AREA** to determine ease of use and desired results. WPC750 may etch, lighten or change the color of cementitious materials (concrete) and will etch natural polished stones such as marble. The user must determine the suitability of the product for their intended use.
4. Always protect adjacent surfaces including wood, carpet, metal, landscaping and other incompatible surfaces.
5. It is not necessary to "pre-wet" surface with water before applying.
6. For general cleaning, dilute WPC750 4 parts water to 1- part WPC750. For stronger solutions, reduce the water down to 1-part water to 1 part cleaner – on limestone and cementous surfaces, this will be a very effective proportion that should remove most any stains. Repeated applications will continue to clean. WPC750 can be applied at full strength for difficult stains; allow to sit on the surface for only a short time, 1-2 minutes or when efflorescing stops. When diluting, always add the cleaner to the water, not water to cleaner. Caution, WPC750 can etch surfaces. Do not mix with other substances.
7. Apply solution with brush, or spray. Allow it to sit on average for about 1 - 2 minutes while agitating with stiff nylon or natural bristle brush or white scrub pad to loosen haze, dirt, stains or soil. Do not allow solution to dry on surface. If it dries add water to remove. Repeated applications will continue to clean.
8. Use a clean mop or preferably a wet vac to remove the remaining solution. Thoroughly power wash/hose off cleaned area with clean water to ensure removal of cleaning agents and removed debris.

NEUTRALIZING

WPC750 is acidic. In general sealants require a neutral surface to bond to. Before applying any type of sealer or coating to the surface we recommend neutralizing the surface with a product such as Waypoints' Neutralizing Rinse, WPN100, and allow the surface to dry thoroughly before applying sealer. Most Sealants can be applied directly over an area cleaned by WPC750; however, results are unpredictable; applying a neutralizer insures maximum effectiveness of the sealant. Sealants such as Waypoint's WPR800 and WPS200 do not perform unless the surface is neutralized.

CAUTIONS: DANGER CAUTIONS: This product contains chemical compounds and surfactants. Avoid prolonged contact with skin. If contact is made, wash immediately with soap and water. If ingested, **DO NOT INDUCEVOMITING.** Drink Milk of Magnesia or milk. Call a physician. If contact with your eyes occurs, flush with water for 15 minutes. Call a physician.

KEEP OUT OF REACH OF CHILDREN READ COMPLETE INSTRUCTIONS BEFORE USING HANDLING & STORAGE
Generally use in solution with water; may be used full strength! Store tightly capped in original container to prevent evaporation! Store in cool, dry place.

Storage

Store WPC750 in the original container, properly sealed to avoid contamination and evaporation. Keep in an upright position. Stored at summer temperatures in an unopened container, WPC750 will have a shelf life of 1 – 2 years. Do not allow to freeze.

Coverage

Coverage will vary depending on density, porosity, texture, solution, surface absorption, etc., 200-500 sq ft per gallon can be expected.

Packaging

WPC750 is sold in quarts, gallons, and 5-gallon pails.

Special Notes

Waypoint Sealants makes a variety of products to keep your clean surface looking new:

WPN900 Stain Tuff Sealer is an awesome sealer that will keep most outdoor patio, driveway, and swimming pool surrounds free from mother nature's stains and many household stains as well as repelling oil and water penetration without affecting the surface color.

WPC100 Surface Clear HD is the only product of its kind. It will keep black algae/mold from coming back on a treated surface for a full 5 – 7 years as well as preventing water penetration. This product is awesome on limestone and concrete which blacken in most climates.

WPR800 Ultra Enhancer WB is a penetrating sealer that will enhance the color of stone while leaving a matte finish. Additional coats darken the surface bringing out the rich colors.

Waypoint Sealant's Acrylic Products protect the surface from just about any stain while giving the substrate a rich wet look.

WARRANTY

The information and recommendations made are based on our own research and the research of others and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application of our products, nor anticipate every variation encountered in natural stone and masonry surfaces, job conditions, and methods used for application. The purchasers shall make their own tests to determine the suitability of such products for a particular purpose.

WAYPOINT SEALANTS warrants this product to be free from defects. Where permitted by law, WAYPOINT SEALANTS makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for a particular purpose. WAYPOINT'S liability shall be limited in all events to supplying sufficient product to re-treat the specific areas to which defective product has been applied. Acceptance and use of this product absolves WAYPOINT SEALANTS from any other liability, from whatever source, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be modified or extended by representatives of WAYPOINT, its distributors or dealers.

CUSTOMER CARE

Factory personnel are available for product, environment and job-safety assistance with no obligation. Call 877-333-8188 Customer Care - technical support. Please visit our website at www.waypointsealants.com

Physical Properties	
Appearance:	Clear
Physical State:	Liquid
Color:	Colorless
Odor:	Light Sweet Odor
pH:	>pH 2 neat
Flash Point:	>200.0F. (closed cup)
Evaporation Rate:	Slow
Vapor Pressure:	0.94 hpa
Pounds Per Gal	7.87
Specific Gravity	1.09